

MPPT 100/40 (40 A)


MPPT Charge Controller



phocos



Technical Drawing



Product Introduction

With innovative maximum power point tracking technology, Phocos' MPPT 100/40 ensures optimal performance from the solar array at all times and in all weather conditions. Innovative MPPT charging can yield an energy gain from your PV array of up to 30%.

The temperature-compensated three-stage I/V curve charge algorithm significantly extends the lifespan of the battery.

Power+™ current limiting allows for over-sizing PV power by up to 50% for winter months.

Product Features

- Thermal overload protection and temperature compensation
- Equipped with a short circuit disconnect function
- Works in 12 or 24 V systems
- Use as a stand alone 40 A controller or part of modular system (MCU required)
- Faster recharging by converting excess PV voltage to charge current
- Highest charging efficiency in low irradiation conditions

Optional Accessories

MCU

- Modular Central Unit
- System voltage 12/24/48 V selectable

MXI

- Interface for communication with computer USB interface

MPS

- Modular Power Switch
- Auto recognition of system voltage 12/24/48 V
- Max. charge current: 45/80A versions

MODCOM

- Application software for MCU communication with computer

MCS

- Modular Current Sensor
- System voltage 12/24/48 V
- RS485 socket

- Current measurement range 50/100/200/400/800 A

MTS

- External temp. sensor for MCU

MRD

- Remote display for MCU
- Displays panel current, load current and battery voltage, Ah, SOC, etc.

MXI 232

- Interface for M 112150180 CU RS232 interface communication with computer

Technical Data

Type	MPPT 100/40 (40A)
System Voltage	12/24 V auto recognition
Nominal Charge Current	40 A
Max. Battery Charge Current	41 A
Float Charge	13.8/27.6 V (25 °C)
Main Charge	14.4/28.8 V (25 °C), 0.5 h daily
Boost Charge/Activation	14.4/28.8 V (25 °C), 2 h battery voltage < 12.3/24.6 V
Equalization Charge/Activation	14.8/29.6 V (25 °C), 2 h battery voltage < 12.1/24.2 V (at east every 30 days)
Max. Battery Voltage	32 V
Max. PV Voltage	95 V
Min. PV Voltage	17/34 V
Max. PV Input Power	800 W/1600 W
Standby Power Consumption	< 30 mW (< 2 mA)/ < 80 mW (< 3 mA)
Temperature Compensation	-25 mV/K (12 V); -50 mV/K (24 V)
Power Conversion Efficiency	Up to 98%
Grounding	Negative grounded
Ambient Temperature	-40 to +45°C
Battery Type	Lead acid (gel, AGM, flooded)
Wire Cross Section	33 mm ² (AWG 2)
Dimensions (WxHxD)	185 x 150 x 115 mm / 7.3 x 6 x 4.5 in
Weight	1.6 kg / 3.5 lbs
Ingress Protection	IP20
Certificates	CE compliant, RoHS compliant
Warranty	5 years